



Juniper Networks Firewall/VPN Products	Interfaces	Max Throughput	Max Sessions	Max VPN Tunnels	Max Policies	Virtual Systems	Virtual LANs	Security Zones	Virtual Routers	High Availability ²	Routing	Deep Inspection / IDP	Integrated Antivirus ³	Integrated Anti-Spam	Web Filtering (Integrated/External)
NetScreen-5400 ⁴	8 mini-GBIC (SX, LX or TX), or 2 XFP 10Gig (SR or LR)	30 Gb firewall 15 Gb AES VPN	1,000,000	25,000	40,000	Up to 500	4,000	16 + up to 1,000 addtl ⁵	3 + up to 500 addtl ⁵	A/P, A/A, F/M	OSPF, BGP, RIPv1/v2	Yes / No	No	No	No / Yes
NetScreen-5200 ⁴	8 mini-GBIC (SX, LX or TX), or 2 XFP 10Gig (SR or LR)	10 Gb firewall 5 Gb AES VPN	1,000,000	25,000	40,000	Up to 500	4,000	16 + up to 1,000 addtl ⁵	3 + up to 500 addtl ⁵	A/P, A/A, F/M	OSPF, BGP, RIPv1/v2	Yes / No	No	No	No / Yes
ISG 2000 w/optional IDP	Up to 16 mini-GBIC (SX, LX or TX), up to 8 10/100/1000, up to 28 10/100	4 Gb firewall 2 Gb 3DES VPN	1,000,000 ⁶	10,000	30,000	Up to 250	2,000 ⁶	26 + up to 500 addtl ⁵	3 + up to 250 addtl ⁵	A/P, A/A, F/M	OSPF, BGP, RIPv1/v2	Yes / Yes	No	Yes	Yes / Yes
ISG 1000 w/optional IDP	Up to 8 mini-GBIC (SX, LX or TX), up to 8 10/100/1000, up to 20 10/100	1 Gb firewall 1 Gb 3DES VPN	500,000 ⁶	2,000	10,000	Up to 50	1,000 ⁶	20 + up to 100 addtl ⁵	3 + up to 50 addtl ⁵	A/P, A/A, F/M	OSPF, BGP, RIPv1/v2	Yes / Yes	No	Yes	Yes / Yes
NetScreen-500 ⁴	Up to 8 10/100 or 8 Mini- GBIC OR 4 GBIC	700 Mb firewall 250 Mb 3DES VPN	250,000	5,000 + 10,000 Dial-up	20,000	Up to 25	100	8 + up to 50 addtl ⁵	3 + up to 25 addtl ⁵	A/P, A/A, F/M	OSPF, BGP, RIPv1/v2	Yes / Yes	No	No	No / Yes
SSG 550M	4 10/100/1000 and 6 I/O slots, supporting SFP, FE, Serial, T1/E1, DS3, E3, ADSL2+, G.SHDSL, 10/100/1000	1+ Gb firewall 500 Mb 3DES VPN 600,000 Packets per second	128,000	1,000	4,000	N/A	150	60	8	A/P, A/A	OSPF, BGP, RIPv1/v2, along with Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, HDLC	Yes / No	Yes	Yes	Yes / Yes
SSG 520M	4 10/100/1000 and 6 I/O slots, supporting SFP, FE, Serial, T1/E1, DS3, E3, ADSL2+, G.SHDSL, 10/100/1000	650+ Mb firewall 300 Mb 3DES VPN 300,000 Packets per second	64,000	500	1,000	N/A	125	60	5	A/P, A/A	OSPF, BGP, RIPv1/v2, along with Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, HDLC	Yes / No	Yes	Yes	Yes / Yes
SSG 350M	4 10/100/1000 and 5 I/O slots supporting Serial, T1/E1, ADSL, ADSL2, ADSL2+, G.SHDSL	550+ Mb firewall 225 Mb 3DES VPN 225000 packets per sec	48,000	350	750	N/A	125	40	8	A/P, A/A	OSPF, BGP, RIPv1/v2, along with Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, HDLC	Yes / No	Yes	Yes	Yes / Yes
SSG 320M	4 10/100/1000 and 3 I/O slots supporting Serial, T1/E1, ADSL, ADSL2, ADSL2+, G.SHDSL	450+ Mb firewall 175 Mb 3DES VPN 175000 packets per sec	48,000	250	750	N/A	125	40	5	A/P, A/A	OSPF, BGP, RIPv1/v2, along with Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, HDLC	Yes / No	Yes	Yes	Yes / Yes
NetScreen-204/208 ⁴	4 10/100 (NS-204) 8 10/100 (NS-208)	375 Mb firewall 175 Mb 3DES VPN	128,000	1,000	4,000	N/A	32 + up to 96 addtl ⁵	4 + up to 10 addtl ⁵ (NS-204) 8 + up to 10 addtl ⁵ (NS-208)	3 + up to 5 addtl ⁵	A/P, A/A (NS-204) A/P, A/A, F/M (NS-208)	OSPF, BGP, RIPv1/v2	Yes / No	No	No	No / Yes
NetScreen-50	4 10/100	170 Mb firewall 45 Mb 3DES VPN	64,000	500	1,000	N/A	16	4	3	A/P	OSPF, BGP, RIPv1/v2	Yes / No	No	Yes	Yes / Yes
SSG 140	8 10/100 + 2 10/100/1000 + 4 I/O slots supporting T1, E1, ISDN BRI S/T, Serial, ADSL2+, G.SHDSL, 10/100/1000, SFP	350+ Mb firewall 100 Mb 3DES VPN	32,000	125	500	N/A	100	40	3	A/P, A/A	OSPF, BGP, RIPv1/v2, along with Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, HDLC	Yes / No	Yes	Yes	Yes / Yes
NetScreen-25	4 10/100	100 Mb firewall 20 Mb 3DES VPN	32,000	125	500	N/A	16	4	3	H/A Lite	OSPF, BGP, RIPv1/v2	Yes / No	No	Yes	Yes / Yes
SSG 20 SSG 20 Wireless	5 10/100 + 2 I/O slots supporting T1, E1, V.92, ISDN BRI S/T, SFP, Serial, or ADSL2+, Optional 802.11a/b/g	160 Mb firewall 90 Mb 3DES VPN	4,000/ 8,000 ⁷	25/40 ⁷	200	N/A	10/50 ⁷	8	3	Dial Backup, A/P ⁸ , A/A	OSPF, BGP, RIPv1/v2, along with Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, HDLC	Yes / No	Yes	Yes	Yes / Yes
SSG 5 SSG 5 Wireless	7 10/100 with Factory Configured V.92 or ISDN BRI S/T or RS232 Serial/AUX, Optional 802.11a/b/g	160 Mb firewall 90 Mb 3DES VPN	4,000/ 8,000 ⁷	25/40 ⁷	200	N/A	10/50 ⁷	8	3	Dial Backup, A/P ⁸ , A/A	OSPF, BGP, RIPv1/v2, along with PPP	Yes / No	Yes	Yes	Yes / Yes
NetScreen-5GT NetScreen-5GT ADSL NetScreen-5GT Wireless	5 10/100 + Factory Configured ADSL and/or 802.11b/g	75 Mb firewall 20 Mb 3DES VPN	2,000	10	100	N/A	N/A	2 (3 with home /work zones) 4 (NS 5GT Wireless)	3	Dial Backup	OSPF, BGP, RIPv1/v2	Yes / No	Yes	Yes	Yes / Yes
NetScreen-5XT ⁴	5 10/100	70 Mb firewall 20 Mb 3DES VPN	2,000	10	100	N/A	N/A	2 (3 with home /work zones)	2	Dial Backup	OSPF, BGP, RIPv1/v2	Yes / No	No	No	No / Yes
NetScreen-Hardware Security Client	5 10/100	50 Mb firewall 10 Mb 3DES VPN	1,000	2	50	N/A	N/A	2 (3 with home /work zones)	2	No	RIPv1/v2	Yes / No	Yes	Yes	Yes / Yes

Juniper Networks IDP Products	Max Throughput	Max Sessions	Operational Modes	Detection Mechanisms	Signature Updates	Interfaces	High Availability
IDP 1100C / 1100F	1 Gb	500,000	Passive sniffer Inline bridge Inline Proxy-ARP Inline router	8 including Stateful Signatures, Protocol Anomalies and Backdoor Detection	Daily and emergency	10 CG or 8 Fiber SX + 2 CG traffic, 1 CG mgmt & 1 CG HA ports	Integrated bypass for copper gigabit traffic ports; Load sharing Clustering 3rd party failover
IDP 600C / 600F	500 Mb	220,000				10 CG or 8 Fiber SX + 2 CG traffic, 1 CG mgmt & 1 CG HA ports	
IDP 200	250 Mb	70,000				8 CG traffic, 1 CG mgmt & 1 CG HA ports	
IDP 50	50 Mb	10,000				2 CG traffic + 1 CG mgmt ports	Integrated bypass

Juniper Networks SSL VPN Products	Market Segment	Users	Access Method	Interfaces	High Availability
SA 700	Small to mid-size enterprises <250 total employees	Remote or mobile employees, business partners, customers	· Clientless Core Web Access · Network Connect	2 RJ-45, 10/100	N/A
SA 2000	Small to mid-size enterprises		· Clientless Core Web Access · Secure App. Manager · Network Connect	2 RJ-45, 10/100/1000	A/P, A/A, Stateful Peering, Clustering
SA 4000	Mid-size to large enterprises			2 RJ-45, 10/100/1000 traffic; 1 RJ-45 10/100/1000 mgmt; 2 SFP GigE ports	
SA 6000	Large enterprises				
SA 6000 SP	Large enterprises / Service providers			Plus redundant power supply, hard drive w/ real-time data mirroring, & additional memory	

Juniper Networks Infranet Controllers are the hardened, centralized policy servers at the heart of Juniper Networks Unified Access Control (UAC), which delivers a standards-based, comprehensive network and application access control solution that combines user identity, device security and health state, and location information for session-specific access policy by user, leveraging existing network investments, including AAA infrastructure, 802.1X switches or access points, and/or Juniper Networks firewalls.

Infranet Controller Models	Market Segment	Enforcement Points	Concurrent Endpoints	Interfaces	High Availability
Infranet Controller (IC) 6000	Large Enterprise	· Juniper Networks FW/VPN Products with ScreenOS 5.4 · Any vendor's 802.1X-enabled switch/access point	Up to 25,000	2RJ-45, 10/100/1000	Clustering, hot swappable power supply
Infranet Controller (IC) 4000	Medium Enterprise or Remote/Branch Office		Up to 3,000	2RJ-45, 10/100/1000	Clustering

1) High Availability definitions: A/P = Active / Passive mode, A/A = Active / Active mode, F/M = Active / Active full mesh mode, H/A Lite = FW and VPN failover without session synchronization

2) Requires purchase of virtual system key; Every virtual system includes one virtual router and two security zones, usable in the virtual or root system

3) 96 VLANs, 10 security zones and 5 virtual routers can be added to the NetScreen-200 series with the purchase of a virtualization key

4) Please visit <http://csrc.nist.gov/cryptval/140-1/1401vend.htm> for FIPS 140-2 certificates for these platforms.

5) The Juniper-Kaspersky Antivirus engine includes protection against Spyware, Adware, and Phishing attacks.

6) Max Sessions listed based on optional IDP upgrade. FW/VPN Max Sessions without optional IDP upgrade are 250,000 for the ISG 1000 and 500,000 for the ISG 2000. VLAN Maximums are 250 for the ISG 1000 and 500 for the ISG 2000

7) Increased Session, VPN tunnel, VLAN capacities and A/P HA and HA Lite require an Extended License key.



CORPORATE HEADQUARTERS
AND SALES HEADQUARTERS
FOR NORTH AND SOUTH AMERICA
Juniper Networks, Inc.
1194 North Mathilda Avenue
Sunnyvale, CA 94089 USA
Phone: 888.JUNIPER (888.586.4737)
or 408.745.2000
Fax: 408.745.2100
www.juniper.net

EAST COAST OFFICE
Juniper Networks, Inc.
10 Technology Park Drive
Westford, MA 01886-3146 USA
Phone: 978.589.5800
Fax: 978.589.0800

ASIA PACIFIC REGIONAL
SALES HEADQUARTERS
Juniper Networks (Hong Kong) Ltd.
Suite 2507-11, 25/F
ICBC Tower
Citibank Plaza, 3 Garden Road
Central, Hong Kong
Phone: 852.2332.3636
Fax: 852.2574.7803

EUROPE, MIDDLE EAST, AFRICA
REGIONAL SALES HEADQUARTERS
Juniper Networks (UK) Limited
Building 1
Aviator Park
Station Road
Aldrestone
Surrey, KT15 2PG, U.K.
Phone: 44.(0).1372.385500
Fax: 44.(0).1372.385501

Copyright 2007 Juniper Networks, Inc. All rights reserved. Juniper Networks, the Juniper Networks logo, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. JUNOS and JUNOSe are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners. Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.